## **BÖKER** SPRÜHKLEBERSYSTEME GMbH

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking:

#### 1.1 Product identifier:

Trade name: GLUKON multi (Druckbehälter) UFI: CNC5-WJ7R-2N08-730T

**1.2 Relevant identified uses of the substance or mixture and uses advised against:** No further relevant information available.

Application of the substance / the preparation: Industrial adhesive spray - for industrial use only

1.3 Details of the supplier of the safety data sheet: Manufacturer/Supplier: BÖKER Sprühklebersysteme GmbH Wegkamp 1 24589 Dätgen

Fon +49 (0) 4329-91128-0 Fax +49 (0) 4329-91128-29 E-Mail: info@glukon.de www.glukon.de

**Further information obtainable from:** BÖKER Sprühklebersysteme GmbH **1.4 Emergency telephone number:** Giftinformationszentrum-Nord / GIZ-Nord Poisons Centre Telefon / Phone +49 (0) 551/19240 24h / 7d

## **SECTION 2: Hazards identification:**

## 2.1 Classification of the substance or mixture: Classification according to Regulation (EC) No 1272/2008:



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

GHS07

Skin Irrit. 2 H315	Causes skin irritation.
Eye Irrit. 2 H319	Causes serious eye irritation.
STOT SE 3 H336	May cause drowsiness or dizziness.

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008: The product is classified and labelled according to the CLP regulation. Hazard pictograms:



Printing date: 13.12.2023

Signal word: Danger

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

## Trade name: GLUKON multi (Druckbehälter)

(Contd. of page 1)

Signal word. Danger					
Hazard-determining components of labelling: dichloromethane Hazard statements:					
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.					
H315 Causes skin irritation.					
	H351 Suspected of causing cancer. Route of exposure: Inhalation.				
H336 May cause drowsiness or dizziness.					
Precautionary st					
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.				
P211	Do not spray on an open flame or other ignition source.				
P251 Do not pierce or burn, even after use.					
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.					
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.				
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.				
Additional information:					
Restricted to professional users.					
Buildup of explosive mixtures possible without sufficient ventilation.					
2.3 Other hazards:					
Results of PBT and vPvB assessment:					
PBT: Not applicable.					
vPvB: Not applica	vPvB: Not applicable.				

## SECTION 3: Composition/information on ingredients:

## 3.2 Mixtures:

**Description:** Mixture of substances listed below with nonhazardous additions.

#### **Dangerous components:**

CAS: 75-09-2 dichloromethane	30-60%		
EINECS: 200-838-9 🗞 Carc. 2, H351; 🔶 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336			
CAS: 68476-85-7 petroleum gases, liquefied	30-60%		
EINECS: 270-704-2 🚸 Flam. Gas 1A, H220; 🔶 Press. Gas (Comp.), H280			
Additional information: For the wording of the listed hazard phrases refer to section 16.			

## SECTION 4: First aid measures:

#### 4.1 Description of first aid measures:

General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

After inhalation: Supply fresh air; consult doctor in case of complaints.

## After skin contact:

Immediately wash with water and soap and rinse thoroughly.

In cases of frost bites, rinse with plenty of water. Do not remove clothing.

## After eye contact:

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

After swallowing: Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed:

No further relevant information available.

Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

(Contd. of page 2)

## Trade name: GLUKON multi (Druckbehälter)

4.3 Indication of any immediate medical attention and special treatment needed:

Monitor circulation, possible shock treatment. If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

## SECTION 5: Firefighting measures:

5.1 Extinguishing media:

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture:

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Hydrogen chloride (HCl)

5.3 Advice for firefighters:

## **Protective equipment:**

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

## **SECTION 6: Accidental release measures:**

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

#### 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage:**

## 7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e.

electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Fumes can combine with air to form an explosive mixture.

Emergency cooling must be available in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities:

Storage:

**Requirements to be met by storerooms and receptacles:** Store in a cool location.



Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

## Trade name: GLUKON multi (Druckbehälter)

(Contd. of page 3)

Store only in the original receptacle.
Observe official regulations on storing packagings with pressurised containers.
Information about storage in one common storage facility: Store away from foodstuffs.
Further information about storage conditions:
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Storage class: 2 B
7.3 Specific end use(s): No further relevant information available.

## SECTION 8: Exposure controls/personal protection:

## 8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:

## 75-09-2 dichloromethane

OEL Short-term value: 706 mg/m<sup>3</sup>, 200 ppm Long-term value: 353 mg/m<sup>3</sup>, 100 ppm Sk, IEOLV

## 68476-85-7 petroleum gases, liquefied

OEL Short-term value: 2250 mg/m<sup>3</sup>, 1250 ppm Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

## 8.2 Exposure controls:

Appropriate engineering controls: No further data; see section 7. Individual protection measures, such as personal protective equipment: General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

## **Respiratory protection:**

If the occupational exposure limit value (e.g. through adequate ventilation at the workplace or through the work place or a stationary extraction device at the workplace), respiratory protection is not required. required.

The product contains low-boiling substances. In exceptional situations (e.g. unintentional release of substances

release of the substance, exceeding the occupational exposure limit), respiratory protection must be worn. Here is

generally for a short time (observe filter size and breakthrough time) full-face mask with an AX filter insert (e.g. filter no. 6098 from 3M, use only factory-fresh!). For concentrations

above the application limit of filter devices, with oxygen contents below 17 vol% or in unclear conditions conditions, use an insulating device (DIN EN 137, observe wearing time limit).

## Hand protection: Protective gloves

## Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

## Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

As protection from splashes gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

Not suitable are gloves made of the following materials:

Leather gloves



Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

## Trade name: GLUKON multi (Druckbehälter)

Strong material gloves Natural rubber, NR Butyl rubber, BR Nitrile rubber, NBR Chloroprene rubber, CR PVC gloves **Eye/face protection:** Tightly sealed goggles

## SECTION 9: Physical and chemical properties:

	nformation on basic physical and chemical	properties:	
	eral Information:	Aaroool	
	sical state:	Aerosol	
Colo		Amber coloured	
Odou		Characteristic	
	ur threshold:	Not determined.	
	ing point/freezing point:	Undetermined.	
	ng point or initial boiling point and boiling		
rang		Not applicable, as aerosol.	
	mability:	Not applicable.	
	er and upper explosion limit:	4 5 1 4 1 0 /	
Lowe		1.5 Vol %	
Uppe		22.0 Vol %	
	h point:	Not applicable, as aerosol.	
	-ignition temperature:	365 °C	
	omposition temperature:	Not determined.	
pH:		Not determined.	
	osity:		
	matic viscosity:	Not determined.	
Dyna		Not determined.	
	bility:		
wate		Not miscible or difficult to mix.	
	tion coefficient n-octanol/water (log value):		
	our pressure at 20 °C:	8300 hPa	
	sity and/or relative density:		
Dens		Not determined.	
	tive density:	Not determined.	
Vapo	our density:	Not determined.	
9.2 C	Other information:		
	earance:		
Form		Aerosol	
	ortant information on protection of health		
	environment, and on safety.:		
	ion temperature:	Product is not selfigniting.	
	osive properties:	Product is not explosive. However, format	ion of
=//p/		explosive air/vapour mixtures are possible	
Solv	ent content:		
	(EC):	728 g/l	
	nge in condition:		
	poration rate:	Not applicable.	
		[· [· · · · · · · · · ·	
	mation with regard to physical hazard		
class		N7 11	
Expl	osives:	Void	ontd or
			ontd. on



Printing date: 13.12.2023

(Contd. of page 4)

(Contd. on page 6)

## **BÖKER** SPRÜHKLEBERSYSTEME GMBH

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

## Trade name: GLUKON multi (Druckbehälter)

	(Contd. of page 5)	
Flammable gases:	Void	
Aerosols:	Extremely flammable aerosol. Pressurised container:	
	May burst if heated.	
Oxidising gases:	Void	
Gases under pressure:	Void	
Flammable liquids:	Void	
Flammable solids:	Void	
Self-reactive substances and mixtures:	Void	
Pyrophoric liquids:	Void	
Pyrophoric solids:	Void	
Self-heating substances and mixtures:	Void	
Substances and mixtures, which emit flammable		
gases in contact with water:	Void	
Öxidising liquids:	Void	
Oxidising solids:	Void	
Organic peroxides:	Void	
Corrosive to metals:	Void	
Desensitised explosives:	Void	

## **SECTION 10: Stability and reactivity:**

**10.1 Reactivity:** No further relevant information available.

10.2 Chemical stability:

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: Forms explosive gas mixture with air.

**10.4 Conditions to avoid:** No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide Poisonous gases/vapours Hydrogen chloride (HCI)

## **SECTION 11: Toxicological information:**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008: Acute toxicity:** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

#### 75-09-2 dichloromethane

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Inhalative LC50/4 h 86 mg/l /4 h (mouse)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

**Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met. **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

Carcinogenicity:

Suspected of causing cancer. Route of exposure: Inhalation.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

(Contd. of page 6)

## Trade name: GLUKON multi (Druckbehälter)

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards: Endocrine disrupting properties:

None of the ingredients is listed.

## **SECTION 12: Ecological information:**

## 12.1 Toxicity:

Aquatic toxicity: No further relevant information available.

**12.2 Persistence and degradability:** No further relevant information available.

**12.3 Bioaccumulative potential:** No further relevant information available.

**12.4 Mobility in soil:** No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment:

**PBT:** Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties:

The product does not contain substances with endocrine disrupting properties.

## 12.7 Other adverse effects:

Additional ecological information:

**General notes:** 

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## **SECTION 13: Disposal considerations:**

## 13.1 Waste treatment methods:

#### **Recommendation:**

Product: Dispose of in accordance with local regulations.

According to the European Waste Catalogue (EWC), waste code numbers are not product-related but application-related.

Waste code numbers should be assigned by the consumer, if possible in consultation with the waste disposal authorities.

Contaminated packaging: Take empty containers to a recognised waste disposal facility for recovery or disposal. Return empty pressurised containers to the supplier.

Unless otherwise specified: Dispose of as unused product.

## Waste disposal key:

The following waste code numbers are only intended as a recommendation.

Used product:

16 05 04, gases in pressurised containers containing dangerous substances (including halons)

Emptied packaging in accordance with the Packaging Ordinance:

Emptied, uncontaminated packaging of non-hazardous goods can be sent to the collection systems for sales packaging for recycling.

Unused product:

16 05 04, gases containing dangerous substances in pressurised containers (including halons). uncleaned packaging 15 01 10, packaging containing residues of hazardous substances or contaminated by hazardous substances.

## European waste catalogue:

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.



Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

#### Trade name: GLUKON multi (Druckbehälter)

(Contd. of page 7) **SECTION 14: Transport information:** 14.1 UN number or ID number: ADR, IMDG, IATA UN3501 14.2 UN proper shipping name: ADR 3501 CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (PROPANE, DICHLOROMETHANE) IMDG. IATA CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (PROPANE, DICHLOROMETHANE) 14.3 Transport hazard class(es): **ADR** 2 8F Gases. Class: Label: 2.1 IMDG, IATA Class: 2.1 Gases. Label: 2.1 14.4 Packing group: ADR, IMDG, IATA Void 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user: Warning: Gases. **EMS Number:** F-D,S-U Segregation groups: (SGG10) Liquid halogenated hydrocarbons **Stowage Category: Stowage Code:** SW2 Clear of living quarters. 14.7 Maritime transport in bulk according to IMO instruments: Not applicable. Transport/Additional information: **ADR** Limited quantities (LQ): 0 2 Transport category: **Tunnel restriction code:** B/D **UN "Model Regulation":** UN 3501 CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (PROPANE, DICHLOROMETHANE), 2.1

## **SECTION 15: Regulatory information:**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Directive 2012/18/EU: Named dangerous substances - ANNEX I: None of the ingredients is listed. Seveso category: P3a FLAMMABLE AEROSOLS Qualifying quantity (tonnes) for the application of lower-tier requirements: 150 t



Printing date: 13.12.2023

## **BÖKER** SPRÜHKLEBERSYSTEME GmbH

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

(Contd. of page 8)

## Trade name: GLUKON multi (Druckbehälter)

Qualifying quantity (tonnes) for the application of upper-tier requirements: 500 t REGULATION (EC) No 1907/2006 ANNEX XVII: Conditions of restriction: 3, 59

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II:

None of the ingredients is listed.

**REGULATION (EU) 2019/1148:** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)):

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS:

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors:

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors:

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### **Relevant phrases:**

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

#### Training hints:

Employees who use the product have to be trained on risks for health, hygiene, use of individual protection, accident preventive actions, rescue actions, etc.,

#### Department issuing SDS:

ADEEGO GmbH Wildsteig 4A D-42113 Wuppertal Tel. +49 (0) 202 2575700 Fax. +49 (0) 202 2575701 Email: mail@adeego.de www.adeego.de

© Copyright by ADEEGO GmbH Contact: Dr. Axel Deeg Version number of previous version: 1.0 Abbreviations and acronyms: ADR: Accord relatif au transport international des mar

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

Printing date: 13.12.2023

Version number: 2.0 (replaces version 1.0)

Revision: 13.12.2023

#### Trade name: GLUKON multi (Druckbehälter)

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3



(Contd. of page 9)