

Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Trade name: GLUKON premium wmc sea (Druckbehälter)

UFI: X68S-MMN7-SN09-AQQ4

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Application of the substance / the preparation: Industrial adhesive spray - for industrial use only

1.3 Details of the supplier of the safety data sheet:

Manufacturer/Supplier:

BÖKER Sprühklebersysteme GmbH Wegkamp 1 24589 Dätgen

Fon +49 (0) 4329-91128-0 Fax +49 (0) 4329-91128-29 E-Mail: info@glukon.de www.glukon.de

Further information obtainable from: BÖKER Sprühklebersysteme GmbH

1.4 Emergency telephone number:

Giftinformationszentrum-Nord / GIZ-Nord Poisons Centre

Telefon / Phone +49 (0) 551/19240

24h / 7d

SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008:



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:



GHS02

Signal word: Danger **Hazard statements:**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Restricted to professional users.

Buildup of explosive mixtures possible without sufficient ventilation.

(Contd. on page 2)



Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 1)

2.3 Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients:

3.2 Mixtures:

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 109-87-5 dimethoxymethane 30-60%

Reg.nr.: 01-2119664781-31-XXXX

CAS: 115-10-6 dimethyl ether 10-30%

Reg.nr.: 01-2119472128-37

CAS: 68476-85-7 petroleum gases, liquefied 10-30%

SECTION 4: First aid measures:

4.1 Description of first aid measures:

General information:

Take affected persons out into the fresh air. Do not leave affected persons unattended.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

In cases of frost bites, rinse with plenty of water. Do not remove clothing.

After eye contact:

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

After swallowing:

Rinse out mouth and then drink plenty of water.

Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed: Frost bites

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures:

5.1 Extinguishing media:

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture: Can form explosive gas-air mixtures.

5.3 Advice for firefighters:

Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 3)





Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 2)

SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e.

electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Fumes can combine with air to form an explosive mixture.

Emergency cooling must be available in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities:

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Storage class: 2 B

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:

109-87-5 dimethoxymethane

OEL Long-term value: 3100 mg/m³, 1000 ppm

(Contd. on page 4)



Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 3)

115-10-6 dimethyl ether

OEL Long-term value: 1920 mg/m³, 1000 ppm

IOELV

68476-85-7 petroleum gases, liquefied

OEL Short-term value: 2250 mg/m³, 1250 ppm Long-term value: 1800 mg/m³, 1000 ppm

8.2 Exposure controls:

Appropriate engineering controls: No further data; see section 7.

Individual protection measures, such as personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Respiratory protection:

If the occupational exposure limit value (e.g. through adequate ventilation at the workplace or through the work place or a stationary extraction device at the workpiece), respiratory protection is not required.

The product contains low-boiling substances. In exceptional situations (e.g. unintentional release of substances

release of the substance, exceeding the occupational exposure limit), respiratory protection must be worn. Here is

generally for a short time (observe filter size and breakthrough time) full-face mask with an AX filter insert (e.g. filter no. 6098 from 3M, use only factory-fresh!). For concentrations

above the application limit of filter devices, with oxygen contents below 17 vol% or in unclear conditions conditions, use an insulating device (DIN EN 137, observe wearing time limit).

Hand protection: Protective gloves

Material of gloves:

Butyl rubber, BR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

General Information:

Physical state: Aerosol

Colour:Amber colouredOdour:CharacteristicOdour threshold:Not determined.Melting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range: Not applicable, as aerosol.

Flammability: Not applicable.

(Contd. on page 5)



Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023 Printing date: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 4)

Lower and upper explosion limit:

Lower: 3 Vol % (115-10-6 dimethyl ether) **Upper:** 18.6 Vol % (115-10-6 dimethyl ether)

Flash point: Not applicable, as aerosol.

Auto-ignition temperature: 235 °C (109-87-5 dimethoxymethane)

Decomposition temperature: Not determined. pH: Not determined.

Viscosity:

Kinematic viscosity: Not determined. Dynamic: Not determined.

Solubility:

Not miscible or difficult to mix. water:

Partition coefficient n-octanol/water (log value): Not determined. 440 hPa

Vapour pressure at 20 °C:

Density and/or relative density:

Density at 20 °C: 0.9 g/cm³ Relative density: Not determined. Vapour density: Not determined.

9.2 Other information:

Appearance:

Form: Aerosol

Important information on protection of health

and environment, and on safety.:

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

VOC (EC): 556 q/l

Change in condition:

Evaporation rate: Not applicable.

Information with regard to physical hazard

classes:

Void **Explosives:** Flammable gases: Void

Extremely flammable aerosol. Pressurised container: Aerosols:

May burst if heated.

Oxidising gases: Void Gases under pressure: Void Flammable liquids: Void Flammable solids: Void Self-reactive substances and mixtures: Void **Pyrophoric liquids:** Void **Pyrophoric solids:** Void Self-heating substances and mixtures: Void Substances and mixtures, which emit flammable gases in contact with water: Void Oxidising liquids: Void Oxidising solids: Void Organic peroxides: Void Corrosive to metals: Void Desensitised explosives: Void

(Contd. on page 6)





Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 5)

SECTION 10: Stability and reactivity:

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability:

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: Forms explosive gas mixture with air.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Flammable gases/vapours

SECTION 11: Toxicological information:

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Acute toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met. **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards:

Endocrine disrupting properties:

None of the ingredients is listed.

SECTION 12: Ecological information:

12.1 Toxicity:

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties:

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects:

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Recommendation:

Product: Dispose of in accordance with local regulations.

According to the European Waste Catalogue (EWC), waste code numbers are not product-related but

(Contd. on page 7)





Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 6)

application-related.

Waste code numbers should be assigned by the consumer, if possible in consultation with the waste disposal authorities.

Contaminated packaging: Take empty containers to a recognised waste disposal facility for recovery or disposal. Return empty pressurised containers to the supplier.

Unless otherwise specified: Dispose of as unused product.

Waste disposal key:

The following waste code numbers are only intended as a recommendation.

Used product:

16 05 04, gases in pressurised containers containing dangerous substances (including halons)

Emptied packaging in accordance with the Packaging Ordinance:

Emptied, uncontaminated packaging of non-hazardous goods can be sent to the collection systems for sales packaging for recycling.

Unused product:

16 05 04, gases containing dangerous substances in pressurised containers (including halons). uncleaned packaging 15 01 10, packaging containing residues of hazardous substances or contaminated by hazardous substances.

European waste catalogue:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information:

14.1 UN number or ID number:

ADR, IMDG, IATA

14.2 UN proper shipping name:

ADR 3501 CHEMICAL UNDER PRESSURE, FLAMMABLE,

UN3501

N.O.S. (METHYLAL, petroleum gases, liquefied) CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (METHYLAL, petroleum gases, liquefied)

14.3 Transport hazard class(es):

ADR



IMDG, IATA

2 8F Gases. Class:

Label: 2.1

IMDG, IATA



2.1 Gases. Class:

Label: 2.1

14.4 Packing group:

ADR, IMDG, IATA Void

14.5 Environmental hazards: Not applicable. 14.6 Special precautions for user: Warning: Gases.

EMS Number: F-D,S-U **Stowage Category:** D

(Contd. on page 8)



Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 7)

Stowage Code: SW2 Clear of living quarters.

14.7 Maritime transport in bulk according to IMO

instruments: Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ): 0
Transport category: 2
Tunnel restriction code: B/D

UN "Model Regulation": UN 3501 CHEMICAL UNDER PRESSURE,

FLAMMABLE, N.O.S. (METHYLAL, PETROLEUM

GASES, LIQUEFIED), 2.1

SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Directive 2012/18/EU:

Named dangerous substances - ANNEX I: None of the ingredients is listed.

Seveso category: P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements: 150 t Qualifying quantity (tonnes) for the application of upper-tier requirements: 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII: Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical

and electronic equipment - Annex II:

None of the ingredients is listed. **REGULATION (EU) 2019/1148:**

Regulation (EC) No 273/2004 on drug precursors:

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors:

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

Department issuing SDS:

ADEEGO GmbH Wildsteig 4A D-42113 Wuppertal Tel. +49 (0) 202 2575700 Fax. +49 (0) 202 2575701 Email: mail@adeego.de www.adeego.de

© Copyright by ADEEGO GmbH

Contact: Dr. Axel Deeg

Version number of previous version: 1.0

(Contd. on page 9)





Printing date: 19.12.2023 Version number: 2.0 (replaces version 1.0) Revision: 19.12.2023

Trade name: GLUKON premium wmc sea (Druckbehälter)

(Contd. of page 8)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2